

## Performance

5-pin heavy duty cylinder lock for material thickness up to 15 mm. Cylinders and keys of nickel plated brass.

## Function

The lock is equipped with a micro switch that is triggered by the 90° rotation of the cylinder plug. The key turns 90° and can only be removed in locked position.





NORMAL SECURITY



Dimension (mm)









ASSA ABLOY, the global leader in door opening solutions, dedicated to satisfying end-user needs for security, safety and convenience.

ASSA OEM AB P.O. Box 371 SE-631 05 Eskilstuna Sweden

phone +46 (0)16 17 70 00 fax +46 (0)16 17 74 51

Customer support: phone +46 (0)16 17 79 50 fax +46 (0)16 17 70 18 e-mail: csg@assaoem.se

Keys (2 pieces) 491155 000 002 490610 000 057 Large nut

Included in part no: 390590 000 002

Mounting washer 417030 000 002 Micro switch Screws M2 (2 pcs) Screws M2.3 (2 pcs)

Accessories see data sheet "Accessories"

Spare parts see data sheet "Spare Parts"

Technical data for the micro switch

Unipolar alternating function

Adapted for solder connection

## Notes

Cylinder: Brass

Electrical data

2A ~

1A =

Part

064690 000 000 064901 000 000 064929 000 000 Cylinder house: Nickel plated brass

Cam lock without micro switch, part no: 390696 000 002

Part no.

## Material Finish Brass

Steel

Brass

Nickel plated Zinc plated Nickel plated